



## **1604 COOLING SYSTEM CLEANER**

### **DESCRIPTION**

1604 is designed to effectively dissolve iron oxide deposits from multi-metal open recirculating cooling water systems, while at the same time protect the base metal from corrosion.

### **FEATURES AND BENEFITS**

- Removes iron and copper deposits
- Effective at elevated temperatures
- Compatible with multiple metallurgies

### **PRODUCT FEED AND CONTROL**

1604 is normally shot fed. The product is normally added directly from the shipping container. Feeders, piping, and valves should be made of steel, polyethylene, or PVC.

1604 is normally added to the system based on the specific application. The technical specialist servicing the facility will provide specific treatment control levels based on system conditions.

### **PHYSICAL PROPERTIES**

Physical properties of 1604 are shown on the Material Safety Data Sheet (MSDS), a copy of which is available upon request.

### **STORAGE AND HANDLING**

Keep in a tightly closed container. Store indoors. Recommended storage temperature is 50° F - 105° F (10° C - 40° C). Do not reuse container. Dispose of empty container in compliance with federal, state/provincial and local laws and regulations.

### **ENVIRONMENTAL, HEALTH, AND SAFETY**

For detailed information, consult the material safety data sheet (MSDS).

### **PACKAGING**

1604 is available in a wide variety of customized containers and delivery methods.

