



Closed Loop Chemical 2338 WATER TREATMENT FOR CLOSED SYSTEMS

DESCRIPTION

CLOSED LOOP CHEMICAL 2338 (CLC 2338) is a closed water system treatment program in liquid form. The product contains a combination of nitrite, borate, and silicate formulated to minimize corrosion and deposition. CLC 2338 used in both hot and cold systems. It is compatible with glycol heat transfer fluids.

FEATURES AND BENEFITS

- Controls corrosion
- Extends equipment life
- Improves overall equipment efficiency
- Protects multiple metallurgies

PRODUCT FEED AND CONTROL

CLC 233 is normally shot fed. The product is normally fed neat directly from the shipping container. Feeders, piping and valves should be made of steel, polyethylene, or PVC.

Treatment control ranges vary depending on system operating conditions. CLC 2338 is controlled by a nitrite test. The technical specialist servicing the facility will provide specific treatment control levels based on system conditions.

PHYSICAL PROPERTIES

Physical properties of CLC 2338 are shown on the Material Safety Data Sheet (MSDS), a copy of which is available upon request.

STORAGE AND HANDLING

Keep in a tightly closed container. Store indoors. Recommended storage temperature is 50° F - 105° F (10° C - 40° C). Do not reuse container. Dispose of empty container in compliance with federal, state/provincial and local laws and regulations.

ENVIRONMENTAL, HEALTH, AND SAFETY

For detailed information, consult the material safety data sheet (MSDS).