



## **CARBAMATE NON-OXIDIZING COOLING WATER BIOCIDES**

### **DESCRIPTION**

CARBAMATE is used in recirculating cooling water systems and closed loop systems to control microbial growth. The product is effective over a wide pH range against the microorganisms typically found in these systems.

### **FEATURES AND BENEFITS**

- Excellent broad spectrum microbiocide
- Effective over the range of pH's found in typical cooling systems
- Does not adversely affect cooling water treatment components

### **PRODUCT FEED AND CONTROL**

CARBAMATE is normally shot fed according to the label instructions. The technical specialist servicing the facility will provide specific treatment control levels based on system conditions.

CARBAMATE is normally fed neat directly from the shipping container. Tanks, pumps, piping and valves should be made of stainless steel, polyethylene, or PVC.

### **PHYSICAL PROPERTIES**

Physical properties of CARBAMATE are shown on the Material Safety Data Sheet (MSDS), a copy of which is available upon request.

### **STORAGE AND HANDLING**

Keep in a tightly closed container. Store indoors. Recommended storage temperature is 50° F - 105° F (10° C - 40° C). Do not reuse container. Dispose of empty container in compliance with federal, state/provincial and local laws and regulations. Refer to label for specific instructions.

### **ENVIRONMENTAL, HEALTH, AND SAFETY**

For detailed information, consult the material safety data sheet (MSDS).

### **PACKAGING**

CARBAMATE is available in a wide variety of customized containers and delivery methods.