

CLC 1338

COOLING WATER TREATMENT FOR CLOSED SYSTEMS

CLC 1338 is a closed water system treatment program in liquid form. The product contains a combination of nitrite, borate, and silicate formulated to minimize corrosion and deposition. CLC 1338 used in both hot and cold systems. It is compatible with glycol heat transfer fluids.

FEATURES AND BENEFITS

- Controls corrosion
- Extends equipment life
- Improves overall equipment efficiency
- Protects multiple metallurgies

PRODUCT FEED AND CONTROL

CLC 1338 is normally shot fed. The product is normally fed neat directly from the shipping container. Feeders, piping and valves should be made of steel, polyethylene, or PVC.

Treatment control ranges vary depending on system operating conditions. CLC1338 is controlled by a nitrite test. The technical specialist servicing the facility will provide specific treatment control levels based on system conditions.

PHYSICAL PROPERTIES

Physical properties of CLC1338 are shown on the Material Safety Data Sheet (MSDS), a copy of which is available upon request.

STORAGE AND HANDLING

Keep in a tightly closed container. Store indoors. Recommended storage temperature is 50° F - 105° F (10° C - 40° C). Do not reuse container. Dispose of empty container in compliance with federal, state/provincial and local laws and regulations.

ENVIRONMENTAL, HEALTH, AND SAFETY

For detailed information, consult the material safety data sheet (MSDS).

PACKAGING

CLC1338 is available in a wide variety of customized containers and delivery methods.