



TERBUTHYLAZINE NON-OXIDIZING COOLING WATER BIOCIDES

DESCRIPTION

TERBUTHYLAZINE is used in recirculating cooling water systems to inhibit algal growth. The product is effective over a wide pH range and is normally fed in conjunction with a broad spectrum microbiocide.

FEATURES AND BENEFITS

- Excellent algistat
- Does not adversely affect cooling water treatment components
- Compatible with oxidizing biocides

PRODUCT FEED AND CONTROL

TERBUTHYLAZINE is normally shot fed according to the label instructions. The technical specialist servicing the facility will provide specific treatment control levels based on system conditions.

TERBUTHYLAZINE is normally fed neat directly from the shipping container. Tanks, pumps, piping and valves should be made of stainless steel, polyethylene, or PVC.

PHYSICAL PROPERTIES

Physical properties of TERBUTHYLAZINE are shown on the Material Safety Data Sheet (MSDS), a copy of which is available upon request.

STORAGE AND HANDLING

Keep in a tightly closed container. Store indoors. Recommended storage temperature is 50° F - 105° F (10° C - 40° C). Do not reuse container. Dispose of empty container in compliance with federal, state/provincial and local laws and regulations. Refer to label for specific instructions.

ENVIRONMENTAL, HEALTH, AND SAFETY

For detailed information, consult the material safety data sheet (MSDS).

PACKAGING

TERBUTHYLAZINE is available in a wide variety of customized containers and delivery methods.